



## SX-1254-UG Reeded Glass



### Product Details

**SX-1254-UG Reeded Glass** is a polyester film with a 1/2" reeded design that runs along the length of the roll. This 2-mil thick film is supplied with a silicone coated liner which protects the clear, pressure-sensitive adhesive. Recommended for application to interior glass, single- or double-pane, it is ideal for privacy, decorative, or architectural applications.

### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Installation and Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same methods used for installing window tinting films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Distribution and Contact Information

#### Distribution

**SOLYX®** Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

#### Contact Information

Decorative Films, LLC  
1-888-657-5224  
[www.decorativefilm.com](http://www.decorativefilm.com)

### Product Description

#### SX-1254-UG Reeded Glass

Introducing **UltraGreen**, an innovative collection of decorative privacy window films utilizing advanced, VOC-free coating technology and eco-friendly PVC-free materials to create an environmentally responsible product with exceptional performance.

### Specifications

Product Code	SX-1254-UG
Product Family	Geometric
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	12", 48", 60"
Full Roll Length	100 linear feet
Thickness	2 mil
Visible Light Transmission	61%
UV Rejection	43%
Total Solar Reflectance	8%
Total Solar Absorbance	15%

### Product Construction

#### Face Film

2 mil Polyester

#### Adhesive

Clear, Pressure-Sensitive

#### Release Liner

Silicone Coated