

## SOLYX® Glass Finishes SX-1940 One Way Perforated



### Product Description

**SOLYX® SX-1940 One Way Perforated** is a printable white surface polymeric vinyl film with a black adhesive surface on the back, designed for outdoor installation and one-way visibility of advertisement displays.

#### Specifications

|                             |                      |
|-----------------------------|----------------------|
| Product Code                | SX-1940              |
| Product Family              | Specialized Function |
| Film Type                   | Polymeric Vinyl      |
| Adhesive Type               | Pressure-Sensitive   |
| Usage                       | Exterior or Interior |
| Available Width(s)          | 60"                  |
| Full Roll Length            | 162 linear feet      |
| Thickness                   | 8 mil                |
| Visible Light Transmission  | 30%                  |
| UV Transmission             | 30%                  |
| IR Transmission             | 30%                  |
| Total Solar Absorbance      | 32%                  |
| Glare Reduction             | 40%                  |
| Total Solar Energy Rejected | 65%                  |

### Product Construction

#### Face Film

8 mil Polymeric Vinyl

#### Adhesive

Clear, Pressure-Sensitive

#### Release Liner

Silicone Paper

### Product Details

**SOLYX® SX-1940 One Way Perforated** is designed for outdoor applications but can be used indoors as well. The printable white/black perforated PVC material allows for a one-way display application on the white side with adhesive on the black side. This film is supplied with a silicone paper liner which protects the clear, pressure-sensitive adhesive and is ideal for advertisement displays.

#### Properties

**40% open area, 60% printable surface**

Caliper/Gauge: 8 mil (w/liner 15 mil); Ink: UV, Solvent, Latex

Weight: 370g; Perforation: 0.060" (1.5mm) hole diameter

Adhesive: Solvent adhesive on black surface

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Installation and Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

#### Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of interior installation and three (3) years from the date of exterior installation. See warranty information for specific details.

### Product Distribution and Contact Information

#### Distribution

**SOLYX®** Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

#### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)