

# SOLYX® Glass Finishes

# SX-C376 Etchnwhite Random Lines



# **Product Description**

SOLYX® SX-C376 Etchnwhite Random Lines is a striped polyester film with random etched and white stripes. The stripe direction runs down the length of the roll. This product is ideal for semi-obscuring visibility while allowing excellent light transmission.

#### **Specifications**

| op comeanono               |                    |
|----------------------------|--------------------|
| Product Code               | SX-C376            |
| Product Family             | Geometric          |
| Film Type                  | Polyester          |
| Adhesive Type              | Pressure-Sensitive |
| Usage                      | Interior           |
| Available Width(s)         | 48" (1220mm)       |
| Full Roll Length           | 50 linear feet     |
| Thickness                  | 2 mil              |
| Shading Coefficient        | .93                |
| Visible Light Reflection   | 70%                |
| Visible Light Transmission | 33%                |
| UV Transmission            | 24%                |
| Solar Heat Reflection      | 7%                 |
| Solar Heat Transmission    | 76%                |
| Infra-Red Transmission     | 55%                |

## **Product Construction**

## Face Film

2 mil polyester

#### Adhesive

Clear, Pressure-Sensitive, 0.7 – 0.87 mil

## **Release Liner**

Silicone Coated

### **Product Details**

 $SOLYX \otimes SX$ -C376 Etchnwhite Random Lines is a striped film with random etched and white stripes of between <1mm-5mm thickness which run down the length of the roll. It is supplied with a silicone coated liner with a pressure-sensitive adhesive. This polyester film is ideal for privacy, decorative, or architectural applications.

# **Flammability Rating**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code  $^{\rm @}.$ 

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants**This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

# **Installation and Warranty**

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

#### Warranty

This  $\mathbf{SOLYX} \otimes$  product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

## **Product Distribution and Contact Information**

#### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

 $Samples\ submitted\ upon\ request.$ 

# **Contact Information**

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com