

SOLYX® Glass Finishes

SX-C385 Etched Squares



PRODUCT DETAILS

SOLYX® SX-SC385 Etched Squares is a smooth etched square pattern film with 1 3/16" Etched Squares with a tiny etched squares at the intersections. This film is ideal for semi-obscuring direct visibility while allowing excellent light transmission. This film has a silicone liner and pressure-sensitive adhesive. It is perfect for privacy, decorative or architectural applications.

Fire Rating

When applied to glass or plastic surfaces:
 Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0
 UL 94 Rating UL Classification V-O
 Class A 0 -25 Flame Spread Index 0 -450

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24)

Product Description

SOLYX® SX-SC385 Etched Squares is a smooth etched square pattern film with 1 3/16" Etched Squares with a tiny etched squares at the intersections.

Specifications

Product Code	SX-C385
Product Family	Architectural
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	48" (1220mm)
Full Roll Length	54 linear feet
Thickness	2 mil
Shading Coefficient	.93%
Visible Light Reflection	70%
Visible Light Transmission	30%
UV Transmission	24%
Solar Heat Reflection	7%
Solar Heat Transmission	76%
Infra-Red Transmission	39%

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details. 15 year expected life for interior applications

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC. Samples submitted upon request.

Contact Information

Decorative Films, LLC
 1-888-657-5224
www.decorativefilm.com

Product Construction

Face Film

2 mil polyester

Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

Release Liner

1.5 mil Silicone