

# SOLYX® Glass Finishes

# SX-C387 Linen



# **Product Description**

 $SOLYX \$ \ \ \textbf{SX-C387 Linen} \ \ \text{is a polyester film with thin, white} \\ \text{horizontal and vertical lines in a loose pattern simulating linen} \\ \text{material. This product is ideal for semi-obscuring direct visibility while} \\ \text{allowing excellent light transmission.} \\$ 

## **Specifications**

| Product Code               | SX-C387            |
|----------------------------|--------------------|
| Product Family             | Organic            |
| Film Type                  | Polyester          |
| Adhesive Type              | Pressure-Sensitive |
| Usage                      | Interior           |
| Available Width(s)         | 60"                |
| Full Roll Length           | 100 linear feet    |
| Thickness                  | 2 mil              |
| Shading Coefficient        | .93                |
| Visible Light Reflection   | 70%                |
| Visible Light Transmission | 40%                |
| UV Transmission            | 32%                |
| Solar Heat Reflection      | 7%                 |
| Solar Heat Transmission    | 76%                |
| Infra-Red Transmission     | 70%                |

# **Product Construction**

#### Face Film

2 mil Polyester

#### Adhesive

Clear, Pressure-Sensitive, 0.7-0.87 mil

### **Release Liner**

Silicone Coated

#### **Product Details**

 ${f SOLYX}$  **SX-C387 Linen** is a durable polyester film with thin, white horizontal and vertical lines in a loose pattern simulating linen material. Supplied with a silicone coated liner and a pressure-sensitive adhesive, it is ideal for privacy, decorative, or architectural applications.

## **Flammability Rating**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants**This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

# **Installation and Warranty**

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

#### Warranty

This  $SOLYX \otimes$  product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

## **Product Distribution and Contact Information**

#### Distribution

 $SOLYX {\bf \$} \ \, {\bf Decorative \ Films \ \, are \ \, available \ \, through \ \, authorized} \\ \ \, {\bf Installing \ \, Dealers, \ \, Distributors, \ \, or \ \, directly \ \, from \ \, {\bf Decorative \ \, Films, \ \, LLC.} \\$ 

 $Samples\ submitted\ upon\ request.$ 

# **Contact Information**

Decorative Films, LLC 1-888-657-5224

www.decorativefilm.com