

## SOLYX® Glass Finishes SX-SC038 Clear Fan Tail



### Product Description

SOLYX® SX-SC038 Clear Fan Tail is a translucent, embossed, textured film with a 1" x 2" fan-like pattern. This non-adhesive static cling film effectively obscures visibility while allowing excellent light transmission and is fully removable and reusable.

### Specifications

|                            |                           |
|----------------------------|---------------------------|
| Product Code               | SX-SC038                  |
| Product Family             | Geometric                 |
| Film Type                  | Polypropylene             |
| Adhesive Type              | Non-Adhesive Static Cling |
| Usage                      | Interior                  |
| Available Width(s)         | 36"                       |
| Full Roll Length           | 50 linear feet            |
| Thickness                  | 9 mil                     |
| Shading Coefficient        | .93                       |
| Visible Light Reflection   | 70%                       |
| Visible Light Transmission | 46%                       |
| UV Transmission            | 13%                       |
| Solar Heat Reflection      | 7%                        |
| Solar Heat Transmission    | 76%                       |
| Infra-Red Transmission     | 48%                       |

### Product Construction

#### Face Film

6 mil vinyl

#### Adhesive

Non-Adhesive Static Cling

#### Release Liner

Transparent Synthetic

### Product Details

SOLYX® SX-SC038 Clear Fan Tail is a translucent, embossed, textured film with a 1" x 2" fan-like pattern which runs down the length of the roll. This non-adhesive static cling film is made from durable polypropylene and is recommended for application to interior and exterior glass. It is fully removable and reusable and is perfect for privacy, decorative, or architectural applications.

### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Installation and Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. It is applied using the same tools and techniques used for window tinting films.

#### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Distribution and Contact Information

#### Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

#### Contact Information

Decorative Films, LLC

1-888-657-5224

[www.decorativefilm.com](http://www.decorativefilm.com)