

# SOLYX® Glass Finishes

## SX-SC464 Crystal



## **Product Description**

 $SOLYX \otimes SX$ -SC464 Crystal is a beautiful static cling film with an embossed, serrated leaf pattern on a frosted background that obscures visibility, reduces glare, and provides good lighting.

### **Specifications**

| Product Code                | SX-SC464                  |
|-----------------------------|---------------------------|
| Product Family              | Organic                   |
| Film Type                   | Polypropylene             |
| Adhesive Type               | Non-Adhesive Static Cling |
| Usage                       | Interior                  |
| Available Width(s)          | 35"                       |
| Thickness                   | +/-8 mil                  |
| IR Transmission             | 55%                       |
| Visible Light Transmission  | 62%                       |
| UV Transmission             | 11%                       |
| Absorption                  | 42%                       |
| Total Solar Energy Rejected | 56%                       |

#### **Product Construction**

Face Film

8 mil Polypropylene

**Adhesive** 

Non-Adhesive Static Cling

**Release Liner** 

**Transparent Synthetic** 

## **Product Details**

 ${
m SOLYX} \@$  **SX-SC464 Crystal** is a beautiful non-adhesive film with a textured, prismatic, serrated leaf pattern on a frosted background. This fully removable and reusable static cling film is made of durable polypropylene and has a clear release liner. It is recommended for application to interior and exterior glass (inside surface) as well as plastics and polycarbonate sheets. This film reduces glare, adds privacy, and is ideal for decorative or architectural applications.

#### Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

## **Installation and Warranty**

## Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window tinting films.

## Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### **Product Distribution and Contact Information**

#### Distribution

 $SOLYX @ \ \, \text{Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.}$ 

Samples submitted upon request.

### **Contact Information**

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com