

SOLYX® Glass Finishes SX-SC696 Reflections



Product Details

SOLYX® SX-SC696 Reflections is a textured, embossed film with a multifaceted semi-hexagonal pattern that scatters the light for a beautiful effect. This non-adhesive static cling film is made of durable polypropylene and has a clear, removable release liner. It is recommended for application to interior and exterior glass (inside surface) as well as plastics and polycarbonate sheets. This fully removable and reusable film is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Description

SOLYX® SX-SC696 Reflections is a textured, embossed static cling film with a multifaceted semi-hexagonal pattern that scatters the light, effectively obscuring daytime view while allowing excellent light transmission.

Specifications

Product Code	SX-SC696
Product Family	Organic
Film Type	Polypropylene
Adhesive Type	Non-Adhesive Static Cling
Usage	Interior
Available Width(s)	35.5"
Thickness	+/-8 mil
IR Transmission	69%
Visible Light Transmission	70%
UV Transmission	5%
Absorption	45%
Total Solar Energy Rejected	56%

Product Construction

Face Film

8 mil Polypropylene

Adhesive

Non-Adhesive Static Cling

Release Liner

Transparent Synthetic