# decorativefilms

# SOLYX. Glass Finishes SX-SC697 Tranquility Bamboo



# **Product Description**

SOLYX® SX-SC697 Tranquility Bamboo is an embossed static cling film with a subtly colored bamboo design on a frosted, wovenpattern background that provides an obscured view.

### Specifications

| Product Code                | SX-SC697                   |
|-----------------------------|----------------------------|
| Product Family              | Static Cling/Stained Glass |
| Film Type                   | Polypropylene              |
| Adhesive Type               | Non Adhesive Static Cling  |
| Usage                       | Interior                   |
| Available Width(s)          | 35.5″                      |
| Thickness                   | +/-8 mil                   |
| IR Transmission             | 34%                        |
| Visible Light Transmission  | 40%                        |
| UV Transmission             | 5%                         |
| Absorption                  | 28%                        |
| Total Solar Energy Rejected | 50%                        |

# **Product Construction**

Face Film 8 mil Polypropylene

Adhesive Non-Adhesive Static Cling

Release Liner Transparent Synthetic

# **Product Details**

SOLYX® SX-SC697 Tranquility Bamboo is an embossed, textured film with a lovely, subtly colored bamboo design on a frosted, woven-pattern background. Made of durable polypropylene, this non-adhesive static cling film is supplied with a clear, removable release liner and is recommended for application to interior glass, exterior glass (inside surface), plastics, and polycarbonate sheets. This fully removable and reusable prismatic film reduces glare, adds privacy and subtle color, and casts rainbows when light shines through. It is ideal for privacy, decorative, or architectural applications.

#### **Flammability Rating**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code<sup>®</sup>.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

## Installation and Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

#### Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

# **Product Distribution and Contact Information**

#### Distribution

**SOLYX®** Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

#### **Contact Information**

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com