

SOLYX® Glass Finishes SXJ-0582 Matte Dual Dot Gradient



Product Description

SOLYX® SXJ-0582 Matte Dual Dot Gradient is a lightly textured matte polyester film with a dual fading, fine dot pattern which is semi-opaque in the center fading to clear, up and down. It is ideal for providing graduated privacy and good light transmission.

Specifications

| | |
|-----------------------------|-------------------------|
| Product Code | SXJ-0582 |
| Product Family | Gradient |
| Film Type | Polyester |
| Adhesive Type | Pressure-Sensitive |
| Usage | Interior |
| Available Height | 60" |
| Full Roll Length | 100 linear feet (30.5m) |
| Thickness | 2mil |
| Shading Coefficient | 0.55 |
| Visible Light Reflection | 27% |
| Visible Light Transmission | Average - 46% |
| UV Transmission | 2% |
| Total Solar energy Rejected | 38% |
| Solar Energy Absorbed | 25% |
| Infra-Red Transmission | 70% |

Product Construction

Face Film

2mil Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated

Product Details

SOLYX® SXJ-0582 Matte Dual Dot Gradient is a lightly textured matte polyester film with a dual fading, fine dot pattern which is semi-opaque in the center fading to clear, up and down. This durable film is manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive and is designed for application to interior glass, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

NOTE: The dots in this film are larger than the dots in the SXJ-0581 Matte Dual Fine Dot Gradient.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com