SOLYX. Glass Finishes SXJ-0599 Lineage Dual Frost Gradient



Product Description

SOLYX® SXJ-0599 Lineage Dual Frost Gradient is a dual fading gradient of horizontal white matte stripes that gradually reduce in thickness from the center band up and down. It is ideal for semiprivacy while still allowing excellent light transmission.

Specifications

| Product Code | SXJ-0599 |
|-----------------------------|--------------------|
| Product Family | Gradient |
| Film Type | Polyester |
| Adhesive Type | Pressure-Sensitive |
| Usage | Interior |
| Available Height | 60" (or custom) |
| Full Roll Length | 100 linear feet |
| Thickness | 2mil |
| Shading Coefficient | 0.55 |
| Visible Light Reflection | 27% |
| Visible Light Transmission | Average - 62% |
| UV Transmission | 2% |
| Total Solar energy Rejected | 38% |
| Solar Energy Absorbed | 25% |
| Infra-Red Transmission | 70% |
| | |

Product Construction

Face Film 2mil Polyester

Adhesive Clear, Pressure-Sensitive

Release Liner Silicone Coated

Product Details

SOLYX® SXJ-0599 Lineage Dual Frost Gradient is a dual fading polyester gradient of white matte stripes that gradually reduce in thickness from the center band up and down. The center band measures approximately 22 ¾". This durable film is manufactured with a silicone coated liner which protects the clear, pressure-sensitive adhesive and is designed for application to interior glass, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

NOTE: A solid match to this film is SXJ-0550 White Dusted Matte.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code $^{\oplus}$.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This \mathbf{SOLYX} product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Country of Origin: Made in the USA

Contact Information Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com