

SOLYX® Glass Finishes

SXS-M800 Renwave



Product Description

SOLYX® SXS-M800 Renwave is a metalized, opaque film with a pattern of wavy lines that creates a 3D effect. It is ideal for completely obscuring visibility and providing heat and UV rejection.

Specifications

Product Code	SXS-M800
Product Family	Organic
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Width(s)	48"
Full Roll Length	100 linear feet (30.5m)
Thickness	2 mil
Shading Coefficient	0.24
Visible Light Transmission	<1%
UV Transmission	<1%
Total Solar Reflectance	75%
Total Solar Absorbance	38%
Glare Reduction	98%
Total Solar Energy Rejected	82%

Product Construction

Face Film

2 mil Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated

Product Details

SOLYX® SXS-M800 Renwave is a metalized, opaque film with a pattern of wavy lines that creates a 3D effect. Made of durable polyester, it is supplied with a clear silicone coated release liner which protects the clear, pressure-sensitive adhesive. This film is designed for application to interior glass, single- or double-pane, and exterior facing glass (inside surface). It is ideal for privacy, decorative, solar control, or architectural applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com