

SOLYX
UltraGreen® Glass Finishes
SXWF-TWM-UG Transparent White Matte



Product Description

SOLYX® SXWF-TWM-UG Transparent White Matte

Introducing **UltraGreen**, an innovative collection of decorative privacy window films utilizing advanced, VOC-free coating technology and eco-friendly PVC-free materials to create an environmentally responsible product with exceptional performance.

Specifications

Product Code	SXWF-TWM-UG	
Product Family	Frosted	
Film Type	Polyester	
Adhesive Type	Pressure-Sensitive	
Usage	Interior or Exterior	
Available Width(s)	12", 24", 36", 48", 60"	
Full Roll Length	100 linear feet	
Thickness	2 mil	
Visible Light Transmission	53%	ASTM D 1003
UV Transmission	0%	
Infra-Red Transmission	66%	

Product Construction

Face Film

2 mil Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

2 mil Polypropylene, Silicone coated (thickness variation +/- 10%)

Country of Origin: Made in the USA

Product Details

SOLYX® SXWF-TWM-UG Transparent White Matte is a translucent, frosted polyester film with a matte finish. Supplied with a silicone-coated liner which protects the clear, pressure-sensitive adhesive, it is recommended for application to interior, single- or double-pane, and exterior facing glass as well as on exterior applications.

Flammability Rating

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants

This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Features

Dimensional Stability: Good

Temperature Ranges: Minimum application temperature is +40°F. Service temperature range is -40°F to +250°F.

Adhesion: To stainless steel – 40oz. / in. PSTC-1 with 24-hr dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary.

Exterior Durability: Has very good resistance to discoloration caused by UV light.

Water Resistance: Has limited immersion resistance. Test specific application.

Humidity Resistance: Good

Storage Stability: 2-yr shelf life when stored at 70°F and 50% relative humidity.

Installation and Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same tools and techniques used for installing window tinting films.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through authorized Installing Dealers, Distributors, or directly from Decorative Films, LLC. Samples submitted upon request.

Contact Information

Decorative Films, LLC
 1-888-657-5224

www.decorativefilm.com